

Model: 1T-MX-6344

1T-MX-6344 4x4 HDMI Matrix Switcher is designed to allow distribution of four HDMI (or DVI) sources independently to four destinations. The 1T-MX-6344 supports HDMI v1.3 Deep Color (10 bit color) video and new lossless, compressed Dolby TrueHD, Dolby Digital Plus as well as DTS-HD Master Audio digital audio. HDCP is supported and all signal paths are fully buffered to prevent cross talk. Frequency bandwidth is 2.25 Gbps (Single Link) and each input signal is reconstituted into a new signal before being output thereby eliminating any jitter component.

HDTV signals up to 1080p and PC signals up to UXGA signals are supported as well as 480i and 576i SDTV. Special mechanical features include TV One's exclusive locking DC power connector as well as compatibility with locking type HDMI cable connectors. RS-232 and Infrared Remote Control are provided in addition to front panel pushbuttons. Rackmount ears are included.

Specifications

Key Features of the 1T-MX-6344

- 4x4 Matrix HDMI Matrix Routing Switcher
- HDMI v1.3 Compliant
- DVI Compatible (with DVI to HDMI Adapters)
- Full Embedded Digital Audio I/O Support
- PC Resolutions through UXGA
- HD Resolutions through 1080p
- SD Resolutions of 480i and 576i
- RS-232 Interface
- IR Remote Control
- IR Extender
- Rack Mount Kit included

Video Inputs		Mechanical		
HDMI (Note 1)	4x via HDMI Type A Connectors	Size (H-W-D)	1.75"x17.2"x 6.9"(44x438x175mm)	
Video Outputs		Weight (Net)	6.8 lbs (3.1Kgs)	
HDMI (Note 1)	4x via HDMI Type A Connectors	Warranty		
Audio Inputs/Outputs		Limited Warranty	1 Year Parts and Labor	
	Dolby TrueHD, Dolby Digital Plus,	Environmental		
Embedded Audio	DTS-HD	Operating Temp.	0° to +50°C (+32° to +122°F) 10%	
Performance	-	Operating Humidity	to 90%, Non-condensing	
Compliance	HDMI v1.3, HDCP 1.1, DVI 1.0	Storage Temperature	-10° to +60°C (+14° to +140° F)	
Signal Processing	Compensated, Clock Phase	Storage Humidity	10% to 90%, Non-condensing	
5 5	Adjusted	Power Requirement		
Jitter Processing	Reconstituted Signal; Jitter Free	External Power Supply	5VDC - Locking DC	
Color Processing	30 bit (10 bit/color)	Regulatory Approvals	-	
Frequency Bandwidth	2.25Gbps (Single Link)	Switcher Units	FCC, CE, RoHS	
Video Resolutions	480i through 1080p,	Power Supplies	UL, CUL, CE, PSE, GS, RoHS	
	VGA through UXGA	Accessories Included		
Audio Processing	Dolby, DTS 32-192 fs sample,	1x AC Power Adapter	US, UK or European Type	
6	LPCM 7.1, all Channels	1x RC-44	IR Remote Control Unit	
EDID	Auto or Manual Discovery	1x IR Extender		
Cable Distance-Input	20m (66 ft.) (1080p/8 Bit)	1x Rack Mount Kit		
Cable Distance-Output	15m (49 ft.) (1080p/8 Bit)	1x Operations Manual		
Control Methods	Front Panel, RS-232, IR Remote	Product Number		
	(IR Extender included)	1T-MX-6344	HDMI 4x4 Matrix Switcher	
	· · · · · · · · · · · · · · · · · · ·	Notes		
		(1) DVI Compatible by u	(1) DVI Compatible by using HDMI to DVI Adapters.	

Panel Drawings

